

DS-3T0306HP-E/HS

4-Port 100M Unmanaged Hi-PoE Switch



DS-3T0306HP-E/HS switches are layer 2 Hi-PoE switches, providing advanced PoE power supply technology and wider temperature (-30 to 65 °C) design on the basis of high-performance access to ensure stable data upload. The switches support Hi-PoE, long range, port isolation, and PoE watchdog function.

Key Feature

- 3 × 100M PoE ports, 1 × Hi-PoE port, 1 × gigabit RJ45 port and 1 × gigabit SFP Fiber Optical Port.
- IEEE 802.3at/af/bt standard for Hi-PoE port (Max. 60 W PoE output).
- IEEE 802.3at/af standard for PoE ports (Max. 30 W PoE output).
- IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab standard.
- 6 KV surge protection for PoE ports.
- Up to 300 m long-range transmission.
- PoE watchdog to auto detect and restart the cameras that do not respond.
- Port isolation to improve network security.
- Wire-speed forwarding.
- Wider temperature (-30 to 65 °C) design.
- Store-and-forward switching.
- Solid high-strength metal shell.
- Reliable fan-free design.




Specification


Model		DS-3T0306HP-E/HS
Network parameters	Port number	3 × 100M PoE ports, 1 × Hi-PoE port, 1 × gigabit RJ45 port and 1 × gigabit SFP Fiber Optical Port
	Port type	RJ45 port, full duplex, MDI/MDI-X adaptive
	Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z and IEEE 802.3ab
	Forwarding mode	Store-and-forward switching
	Working mode	Standard mode (default), Extend mode, Isolation mode, PoE watchdog mode
	Ports for long-distance transmission	Ports 3 and 4
	MAC address table	2 K
	Switching capacity	4.8 Gbps
	Packet forwarding rate	3.5712 Mpps
	Internal cache	1.0 Mbits
PoE power supply	PoE standard	Port 1: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt Ports 2 to 4: IEEE 802.3af, IEEE 802.3at
	PoE power pin	Ports 1 to 4: Ethernet cables 1/2/3/6 and 4/5/7/8 provide power supply simultaneously.
	PoE port	Ports 2 to 4
	Hi-PoE port	Port 1
	Max. port power	Port 1: 60 W Ports 2 to 4: 30 W
	PoE power budget	60 W
Dialing function	Long range	Ports 3 and 4: up to 300 m.
	Port isolation	Ports 1 to 4: port isolation mode to improve network security.
	PoE watchdog	Ports 1 to 4: auto detect and restart the cameras that do not respond.
General	Shell	Metal material, fan-free design
	Gross weight	0.915 kg (2.02 lb)
	Net weight	0.35 kg (0.77 lb)
	Dimension (L × H × D)	158 mm × 101.2 mm × 31.6 mm (6.22" × 3.98" × 1.24")
	Operating temperature	-30 °C to 65 °C (-22 °F to 149°F)
	Storage temperature	-40 °C to 85 °C (-40 °F to 185 °F)
	Operating humidity	5% to 95% (no condensation)
	Storage humidity	5% to 95% (no condensation)
	Power supply	48 to 57 VDC, 1.35 A Max.
	Power consumption in idle	< 5 W
	Max. power consumption	65 W
	Power source	65 W
Approval	EMC	FCC (47 CFR Part 15, Subpart B); CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010 +A1: 2015); RCM (AS/NZS CISPR 32: 2015); IC (ICES-003: Issue 6, 2016)
	Safety	UL (UL 60950-1); CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013); CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013)
	Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2006)

Physical Interface

Front panel:




Back panel:



Available Model

DS-3T0306HP-E

Dimension (unit: mm)




Typical Application

4-Port 10/100M PoE

10/100M Unmanaged PoE

Pro Series



Distributed by



HIKVISION

Headquarters

No.565 Qianmo Road, Linping District,
Hangzhou 310051, China
T +86-571-8007-0699
overseas@hikvision.com

HIKVISION USA
T +1-509-896-0400
sales.usa@hikvision.com

HIKVISION Australia
T +61-2-9595-4213
sales.au@hikvision.com

HIKVISION India
T +91-22-28420020
sales.in@hikvision.com

HIKVISION Canada
T +1-888-200-1820
sales.canada@hikvision.com

HIKVISION Thailand
T +662-275-0948
sales.thailand@hikvision.com

HIKVISION Europe
T +31-23-5242770
sales.eu@hikvision.com

HIKVISION Italy
T +39-0438-6802
info.it@hikvision.com

HIKVISION Brazil
T +55-11-3310-0350
latinam.support@hikvision.com

HIKVISION Turkey
T +90-2185217070-7071
sales.tr@hikvision.com

HIKVISION Malaysia
T +601-4552-2913
sales.my@hikvision.com

HIKVISION UK & Ireland
T +44-28 302140
sales.uk@hikvision.com

HIKVISION South Africa
Tel: +27 101 3351172
sales.africa@hikvision.com

HIKVISION France
T +33(0)1-85-330-450
info.fr@hikvision.com

HIKVISION Kazakhstan
T +7-727-6730967
info.kazakhstan@hikvision.com

HIKVISION Vietnam
T +84-9-7270809
sales.vn@hikvision.com

HIKVISION UAE
T +971-4-4432080
sales.me@hikvision.com

HIKVISION Singapore
T +65-6589-4716
sg@hikvision.com

HIKVISION Spain
T +34-91-737-15-55
info.es@hikvision.com

HIKVISION Tashkent
T +99-91-1218-9588
info@hikvision.ru

HIKVISION Hong Kong
T +862-2151-1301
info.hk@hikvision.com

HIKVISION Russia
T +7-495-669-67-88
sales.ru@hikvision.com

HIKVISION Korea
T +82-1031-731-8817
sales.korea@hikvision.com

HIKVISION Poland
T +48-22-403-61-50
info.pl@hikvision.com

HIKVISION Indonesia
T +62-21-2934558
Sales.indonesia@hikvision.com

HIKVISION Colombia
sales.colombia@hikvision.com