

Tiandy



TC-R3432 Spec: I/B/K/V3.1 H.265 4HDD 32ch NVR

Lite-K Series



KEY FEATURES

HD Input

- S+265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Support live view, storage, and playback of the connected camera at up to 8MP resolution

HD Output

- 1×HDMI and 1×VGA simultaneous outputs
- HDMI Video output at up to 4K resolution

HD Storage

- 4 SATA interface, up to 10TB for 1 HDD
- S+265 compression effectively reduces the storage space and costs by up to 75%

HD Transmission

- 2×RJ45 self-adaptive 10/100/1000 Mbps network

interface

Various Applications

- Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrade, etc.
- Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA alarms can be realized
- VCA detection alarm is supported
- Web6 supports plug-in free browsing and can preview videos on all browsers
- Support cloud upgrade




SPECIFICATIONS

Input	
Video Input	32-ch
Max Resolution	8MP
Two-way Audio Input	1-ch, 3.5mm
Bandwidth	Income 160Mbps; Outgoing 48Mbps
Output	
HDMI/VGA Output	HDMI 1-ch, 3840x2160, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800 VGA 1-ch, 1920x1080, 1280x720, 1024x768, 1366x768, 1440x900, 1280x800
Screen Split	1/3/4/5/6/7/8/9/10/12/13/16/20A/20B/25/32
Audio Output	1xRCA
Decoding	
Decoding Format	S+265/H.265/H.264
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Preview Capability	2x8MP, 2x6MP, 3x5MP, 4x4MP, 5x3MP, 8x1080P, 16x720P, 32x4CIF
Synchronous Playback	2x8MP, 2x6MP, 3x5MP, 4x4MP, 5x3MP, 8x1080P
Records Encryption	Yes
Hard Disk	
SATA	4 SATA interface for 4 HDDs
Capacity	Up to 10TB for each HDD
eSATA Interface	N/A
Array Type	N/A
External Interface	
Network Interface	2xRJ45 self-adaptive 10/100/1000 Mbps network interface
USB Interface	1xUSB 2.0, 1xUSB 3.0
Serial Interface	N/A
Alarm In/Out	N/A
Network	
Protocol	HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, DHCP, DNS, DDNS, EasyDDNS, NTP, SMTP, SSL, QoS, IPv4, IPv6, IP Filter, Telnet, SSH, RTSP, RTP, RTCP, ARP, SNMP(v1), PPPOE
System Compatibility	ONVIF (PROFILE S/T/G), SDK, P2P
General	
Web Version	Web6
Language	Simplified Chinese, Traditional Chinese, English, Spanish, Italian, Korean, Turkish, Russian, Thai, French, Hebrew, Polish, Dutch, Arabic, Vietnamese, German, Ukrainian
Operating Conditions	-10 ~ 55°C, 10%~90% RH
Power Supply	DC12V 5A
Consumption (without HDD)	≤25W
Chassis	1.5U
Dimensions	75x347x440mm, (2.95x13.66x17.32 inch)
Weight (without HDD)	3.35Kg (7.38lb)


AVAILABLE MODEL

TC-R3432 SPEC: I/B/K/V3.1

DIMENSIONS (Unit: mm)



Physical Interfaces



DISTRIBUTED BY



Tiandy Technologies Co.,Ltd.

Email: sales@tiandy.com

Website: en.tiandy.com

Tel: +86-22-58596178

Fax: +86-22-58596048